OCEFOPUS

OCTOPUS

Contact Us

BUILDING MATERIALS TRADING LLC.

+971 52 264 763, +91 930 798 5965



- octopus.bmt22@gmail.com
 - Deira, Dubai.





ABOUT US

"Octopus Building Material takes pride in being a leading safety shoe company in Dubai, committed to delivering top-notch protective footwear solutions. With a dedication to quality and safety, we strive to provide innovative and comfortable footwear that meets the stringent standards of various industries. Our mission is to safeguard your every step, ensuring the well-being of workers across diverse sectors. Trust Octopus for reliable, durable, and stylish safety shoes that prioritize your safety without compromising on style or comfort."






Safety Fea	tures can be i	dentified on t	he product	label from following markings.
EN ISO 20345	EN ISO 20346	EN ISO 20347	CLASS	ADDITIONAL FEATURES
SB	P8		1/11	Conforms with basic features
SI	P1	1	I	Closed heel area, antistatic properties, energy absorption in heel area, fuel resistant outsole.
SIP	P1	1	1	Like S1 plus resistance to water penetration and water absorption.
\$2	P2	2	I	Like S1 plus penetration resistance profiled outsole.
\$3	P3	3	1	Like S2 plus penetration resistance profiled outsole.
\$4	P4	4	, and the second se	Like S2 plus antistatic, energy absorption in heel area, fuel resistant outsole.
\$5	Р5	5	II	Like S4 plus penetration resistance profiled outsole.

Additional Marking



For right and easy selection, we have given the following identification marks:



CLASS I: Footwear made of leather and other materials with an exception of formed in one piece or vulcanized.

SAFETY FEATURES

Slip Resistance of Protective, Safety & **Occupational Shoes**

In the new European standard, following three slip resistance limits are defined since beginning of 2008 and as per new standard the footwear must fulfill one of these three requirements:

SRA: Slip resistance on floors with ceramic tiles with SLS (Sodium, Laurylether Sulfate) solution.

- SRB: Slip resistance on steel floor with glycerol.
- SRC: Slip resistance on floor with ceramic tiles with SIS and on steel floor with glycerol (SRA+ SRB).

IDENTIFICATION MARKS

OIL RESISTENACE SOLE

WATERPROOF SHOE

COMPOSITE OR STEEL TOECAP

SOFT IMPACT FOAM

LIGHT WEIGHT

HEEL ENERGY ABSORPTION

DGUV 112-191

CLASSIFICATION

- UPPER LEATHER
- (宜)

(≦)



DRAGO	00
Product Code	OTA 2001
Operative Standard	EN : ISO : 20345 : 2011
Design Type	High Ankel
Size Range	39-45 or 05 to 11
Upper	Barton Buffalo Leather
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density
(f) (f)	
COMPOSITE O STEEL TOECAN	



IRON Product Code OTA 2005 Operative EN : ISO : 20345 : 2011 Standard Design Type Derby Size Range 39-45 or 05 to 11 Barton Buffalo Leather Upper Breathable functional Textiles Lining Lining Toe Cap Steel/composite Toe Cap High Abrasion nylon fabric Insocks laminated with EVA PU Single Density/Double Density Sole Œ COMPOSITE OR STEEL TOECAP SLIP RESISTANT OUTSOLE BREATHABLE SOFT IMPACT OIL RESISTENACE SOLE



SIMBA

Product Code	RE 2006
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Derby
Size Range	39-45 or 05 to 11
Upper	Apollo Buffalo Leather
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density













BULLET

Product Code	OTA 2008
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Derby
Size Range	39-45 or 05 to 11
Upper	Barton Buffalo Leather
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric Iaminated with EVA
Sole	PU Single Density/Double Density













Product Code	OTA 2007
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Derby
Size Range	39-45 or 05 to 11
Upper	Barton Buffalo Leather
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density
$\cap \cap$	
	SUP RESISTANT BREATHABLE OIL RESISTENCE SOFT IMPACT



Product Code	OTA 2009
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Derby
Size Range	39-45 or 05 to 11
Upper	Apollo Buffalo Leather
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density



DRAGON PVC

Product Code	OTA 1001
Design Type	Derby
Size Range	39-45 or 05 to 11
Upper	Barton Print Synthetic Upper
Lining	Mesh Lining
Тое Сар	Steel Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	Single Density PVC











VICTOR PVC

Product Code	OTA 1007
Design Type	Derby
Size Range	39-45 or 05 to 11
Upper	Barton Print Synthetic Upper
Lining	Mesh Lining
Тое Сар	Steel Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	Single Density PVC
(A (<	











Product Code	RE 4004
Operative Standard	EN : ISO : 20345 : 2011
Design Type	FLYKNIT Derby
Size Range	39-45 or 05 to 11
Upper	Light Weight & Breathable Fabric
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density
(E) (L)) (※)(씨)(〃) 🛍

CARBON 2

STEEL TOECAP

Product Code	OTA 4005
Operative Standard	EN : ISO : 20345 : 2011
Design Type	FLYKNIT Derby
Size Range	39-45 or 05 to 11
Upper	Light Weight & Breathable Fabric
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density
	R SLIP RESISTANT SOFT IMPACT

OUTSOLE

FOAM

Shoe

UPPER



SPIDER

Product Code	RE 3005
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Sporty Low Ankle
Size Range	39-45 or 05 to 11
Upper	Buffalo Suede Leather with high
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density













RHINO

Product Code	OTA 3006
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Sporty Low Ankle
Size Range	39-45 or 05 to 11
Upper	Buffalo Suede Leather with high
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density

COMPOSITE OR STELL TOECAP











CLEVER	
Product Code	OTA 2010
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Slip-on / Low Ankle
Size Range	39-45 or 05 to 11
Upper	Buffalo CG Leather
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density
COMPOSITE STELL TOEC	

ΡΛΠΤΗΕΒ

Product Code	RE 3008
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Sporty High Ankle
Size Range	39-45 or 05 to 11
Upper	Buffalo Oil Pullup Leather with High Durable Fabric
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density





CΛΡΤΛΙΩ

Product Code	OTA 3010
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Sporty High Ankle
Size Range	39-45 or 05 to 11
Upper	Buffalo Oil Pullup Leather with High Durable Fabric
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric Iaminated with EVA
Sole	PU Single Density/Double Density
\sim	













RANGER

Product Code	OTA 3009
Operative Standard	EN : ISO : 20345 : 2011
Design Type	Long Boot
Size Range	39-45 or 05 to 11
Upper	Buffalo Nubuck Leather
Lining	Breathable functional Textiles Lining
Тое Сар	Steel/composite Toe Cap
Insocks	High Abrasion nylon fabric laminated with EVA
Sole	PU Single Density/Double Density









